



Date: 11.04.2025

Tender Ref No. III/WATERPROOFING OF TERRACE/2024-25

Tender Date: April 3, 2025

Re: Request for Proposal for Waterproofing Terraces in Six-storied building of our office premise.

Pg. No	Sr. No	Tender Particulars	Amendment
2	4	<b>4. PERFORMANCE SECURITY DEPOSIT:</b> The successful bidder shall have to deposit a Performance Security Deposit of the 10% (approx.) of the total amount of purchase order within three (3) weeks of the receipt of the Work Order. The performance security deposit shall be furnished in the form of Bank Guarantee / Demand draft/ Banker's Cheque of any Nationalized / Private Bank drawn in favour of "Insurance Institute of India" payable at Mumbai. The performance security deposit should be valid for 5 years.	<b>4. PERFORMANCE SECURITY DEPOSIT:</b> The successful bidder shall have to deposit a Performance Security Deposit of the 5% (approx.) of the total amount of purchase order within three (3) weeks of the receipt of the Work Order. The performance security deposit shall be furnished in the form of Bank Guarantee / Demand draft/ Banker's Cheque of any Nationalized / Private Bank drawn in favour of "Insurance Institute of India" payable at Mumbai. The performance security deposit should be valid for 3 years.
8	1	<b>1. PRE BID MEETING:</b> The entrance to the Pre Bid Meeting will be limited to two persons per bidder and carrying valid authorization letter on official letterhead bearing company seal for those who will submit the tender document fee before the Pre Bid Meeting.	<b>1. PRE BID MEETING:</b> No tender document fee.
18	34 b	<b>34. OPENING OF BIDS BY THE INSTITUTE:</b> b) <u>Evaluation of the bids:</u> After the closing time of submission, the Institute will verify the submission of Bid Processing Fees & EMD as per bid terms and conditions. The bids of the bidders will be opened and evaluated by the Institute and successful bidder will be decided as per evaluation criteria.	<b>34. OPENING OF BIDS BY THE INSTITUTE:</b> No tender document fee.
5	3	Providing and application of Nitobond TPE Tape as sandwich membrane at all intersection of pedestal and roof slab. A V-groove (10 x 12 mm) shall of specified dimensions shall be cut along the line of construction joints and filling the same with PU sealant. All the dust, dirt, loose particles etc. shall be removed. The cracks and honeycombs shall be repaired by epoxy putty/ epoxy repair mortar Nitocote VF/ Nitomortar FC. 500 R.ft. to 1000 R.ft Approx.	Quote for 1000 R.ft Approx.

Secretary (Estb.)